

HOSE ASSEMBLIES

PREMIUM & EXTRUDED WRAPPED HOSES

Strahman hoses provide industrial strength for heavy-duty use for washdown and cleaning operations. All our hoses are made with materials that comply with FDA regulations for use in applications where the hose will come in contact with food products. The non-toxic liner meets FDA CFR Title 21, item 177.2600 for fatty food and IANESCO certificate nr. 10/11358 for milk and yogurt.

Strahman hoses come with a standard swivel adapter and assembled with your choice of bronze or stainless steel fittings on the ends of the hose and are ready to be connected to equipment. Optional Internal Spring Assembly is available for added durability. Available standard lengths are 25', 50', 75', and 100' and any size in between we can custom cut. Hoses are not approved for steam service.

PREMIUM WRAPPED HOSE ASSEMBLY

- Made from Neoprene—does not degrade as quickly as natural rubber
- High pressure, homo-flex hot water hose
- Braided construction resists kinks but remains flexible
- Excellent abrasion and tear resistance, practically indestructible
- Resists oil and fatty foods
- Water Temp. Rating -20° to maximum of 200° F (-29° to 93°C)
- Maximum Working Pressure: 150psi
- Available in choice of: Red, White, and Black

EXTRUDED HOSE ASSEMBLY

- Made from Neoprene—does not degrade as quickly as natural rubber
- Lightweight and flexible high pressure hot water hose
- Excellent abrasion and tear resistance
- Resists oil, fatty and lactic acids
- Water Temp. Rating -20° to maximum of 200° F (-29° to 93°C)
- Max. Working Pressure: 150psi
- Available in choice of: Yellow, White, and Black



AVAILABLE OPTIONS INCLUDE:



BRONZE OR STAINLESS STEEL FITTINGS



SWIVEL ADAPTERS



HOSE ASSEMBLIES WITH BALL STOP